



ELECTRICAL CHARACTERISTICS: (FOR CWC9035 COMPATIBLE)

1. D.C.R. : PIN 1-3 = 86 OHM +/-15% PIN 4-6 = 108 OHM +/-15%
2. INDUCTANCE (@1KHZ, 0.25Vrms SERIES): PIN 1-3 = 4.5H MIN.
3. RETURN LOSS : (REF. 600 OHM) 200 TO 4KHZ = 30dB MIN.
4. INSERTION LOSS : (1KHZ, 0dBm 600 OHM LOAD) 1.4dB MAX.
5. FREQ. RESPONSE : (REF. 1KHZ) @100HZ = +/-0.1dB @4KHZ = +/-0.05dB
6. LONGITUDINAL BALANCE : (200HZ - 4KHZ) 70dB MIN.
7. TURNS RATIO :(6KHZ, 1Vrms) PIN 1-3 : 4-6 = 1+/-1%
8. T.H.D. (@600HZ, -10dBm) = -80dB MAX.  
(@200HZ, -3dBm)=-75dB MAX.
9. HI-POT : (@3000VAC, 1mA, 2SEC.) PIN 1-6

						<b>Atech</b> <sup>®</sup>		TITLE 600 : 412 TRANSFORMER	
						Atech Technology Co., Ltd.		DWG. NO. ATS-279	
A ADD BAPT NO.		08/21/98	PAIR		SUEDY	UNITS M/M		SAFETY CRC.0061	
RELEASE		03/30/98	PAIR		SUEDY	DATE 03/30/98		SHEET 1 OF 1	
NO.	DESCRIPTION	DATE	BY	CHK	APPD			DRAW <i>Pair</i>	
REVISIONS									